

| Project: | | | |
|---------------|--|--|--|
| Fixture Type: | | | |
| Location: | | | |
| Contact: | | | |

One-Light Pendant W/HAL AC LED Module

Ceiling cord mounted · Dry location listed PROGRESS LED





Description:

The simple design of this LED Dome pendant offers complements a wide array of styles from industrial to farmhouse. The 9w LED pendant is 3000K in a Satin Aluminum finish with a painted silver interior.

Specifications:

- Satin Aluminum (-16) (powder coat paint)
- Aluminum Construction
- Satin Aluminum, painted silver inside aluminum shade, White acrylic Diffuser
- · LED Module is replaceable (part # 93054049)
- · Inspired to enhance modern home decor.
- · Complements a wide array of styles from industrial to farmhouse.
- Satin Aluminum finish with a painted silver interior.
- · Dimmable to 10% with many ELV dimmers
- 623 lumens 69.2 lumens/watt per module (source)
- 3000K color temperature, 90+ CRI.
- Dimmable to 10% brightness (See Dimming Notes)
- Canopy covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 10 feet of wire supplied
- ENERGY STAR® qualified

Performance:

| Number of Modules | 1 |
|------------------------|-------------------------------------|
| Input Power | 9w |
| Input Voltage | 120 V |
| Input Frequency | 60 Hz |
| Lumens/LPW (Source) | 623/69.2 (LM-82) |
| Lumens/LPW (Delivered) | 388/51.7 (LM-79) |
| CCT | 3000 K |
| CRI | 90+ |
| Life (hours) | 60,000 (L70/TM-21) |
| FCC | Meets FCC Title 47, Part 15 Class B |
| Min. Start Temp | -30 °C |
| Max. Operating Temp | 30 °C |
| Warranty | 5 year warranty |
| Labels | cCSAus Dry location listed |
| | ENERGY STAR® qualified |
| | |

P5340-1630K9

Images:



Dimensions:

Diameter: 10" Height: 5-5/8"

Glass

Overall Ht. W/Cord: 125-1/2"

Width: 10" Length: 10" Glass 2 Width: 2-7/8" Length: 2-7/8" Height: 0-13/16"



One-Light Pendant W/HAL AC LED Module

Ceiling cord mounted • Dry location listed PROGRESS LED





P5340-1630K9

Dimming Notes:

P5340 is designed to be compatible with many ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls

Lutron Nova T NTELV-300

Lutron Vierti VTELV-600

Lutron Ariadni AYCL-153P

Lutron Diva DVCL-153P

Lutron Maestro MAELV-600

Lutron spacer/system SPSELV-600

Leviton Renoir II AWRMG-EAW

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.